

AquaSorb 2000 Series - Activated Carbon

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : AquaSorb 2000 Series
Product code : Activated Carbon.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use as an adsorbent in industrial, professional and consumer setting.

Use descriptor system (REACH) :

SU3 : PROC 1, 2, 3, 4, 5, 8a, 8b, 9, 14, 15, 22
SU22 : PROC 1, 2, 3, 4, 5, 8a, 8b, 9, 15
SU21 : PC 2, 3, 29, 35, 37, 39

The annexed exposure scenarios provide a complete listing per sector.

1.3. Details of the supplier of the safety data sheet

Registered company name : Jacobi Carbons Ltd.
Address : E12, Croft Court, Moss Estate.WN7 3PT.Leigh, Lancashire.United Kingdom.
Telephone : +44 1942 670 600. Fax : +44 1942 670 605.
msds@jacobi.net
www.jacobi.net

1.4. Emergency telephone number : UK: 111.

Association/Organisation : NHS 111.
Other countries : <https://echa.europa.eu/support/helpdesks>

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

This substance does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.
This substance does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).
This substance does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

No labelling requirements for this substance.

2.3. Other hazards

In the event of dust formed by mechanical action (sanding, sawing, etc..), this dust may cause irritation by inhalation and contact with eyes.

The substance does not fulfil the PBT or vPvP criteria in accordance with annexe XIII of the REACH regulations EC 1907/2006.
May cause CO and CO2 emanations in the event of a fire.

According to the ECHA Guidance on chemical safety assessment, Chapter R11, section R11.1.2.1: "The PBT and vPvB criteria of Annex XIII to the Regulation do not apply to inorganic substances". As Activated Carbon - HDS type is to be considered as an inorganic substance, the PBT assessment is not applicable.

AquaSorb 2000 Series - Activated Carbon

Wet Activated Carbon depletes oxygen from air and, therefore, dangerously low levels of oxygen may be encountered. Whenever workers enter a vessel containing activated carbon, the oxygen content should be determined and work procedures for potentially low oxygen areas should be followed.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Composition :

Identification	Classification (EC) 1272/2008	Note	%
CAS: 7440-44-0 EC: 931-328-0 REACH: 01-2119488894-16-0013 ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS)		[1]	100%

Information on ingredients :

A porous, amorphous, high surface area adsorbent material composed largely of elemental carbon.

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Fresh air, rest.

Obtain medical attention if cough or respiratory symptoms develop.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

Rince with water and soap.

Remove contaminated clothes.

Obtain medical attention if irritation becomes apparent.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

Give at least 1/2 L of water to drink.

Obtain medical attention if gastrointestinal symptoms develop.

Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When large amounts are ingested orally, congestion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Specific and immediate treatment :

N/A

AquaSorb 2000 Series - Activated Carbon

Information for the doctor :

Medications efficiency can be reduced by the adsorbing power of the activated carbon.

SECTION 5 : FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- carbon dioxide (CO₂)
- foam
- powder

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

in the closed areas, in order to avoid the water contamination.

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- other decomposition products for the saturated activated carbon.

After a fire, smoldering hotspots within the activated carbon may be present for a long time.

Activated Carbon which has been allowed to smolder for a long time in a confined space may accumulate carbon monoxide above its lower explosion limit.

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Retrieve the product by mechanical means (sweeping/vacuuming).

6.4. Reference to other sections

See also sections 2 & 8

AquaSorb 2000 Series - Activated Carbon

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the substance is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Prevent dust generation. Apply good working practices and engineering procedures during discharge.

See the exposure controls and personal protection measures in the section 8.

Fire prevention :

Prevent access by unauthorised personnel.

Prevent dust generation.

Keep away from heat sources.

Immediately retrieve the product in case of spilling

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Ensure containment and adequate ventilation.

Whenever workers enter a vessel containing activated carbon, the oxygen content should be determined and work procedures for potentially low oxygen areas should be followed.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the substance is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from any chemical (solvents and strong oxidisers).

Keep away from heat sources.

Store in a well-ventilated area.

Keep the container away from dampness

Storage

Store and keep away from any chemical (solvents and strong oxidisers).

Storage of wet activated carbon in a closed area can deplete oxygen from air.

Packaging

Always keep in packaging made of an identical material to the original.

Store in the closed, original packaging.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7440-44-0	4 mg/m3				

- Non otherwise classified dusts : 10 mg/m3

Biological limits :

/

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS) (CAS: 7440-44-0)

AquaSorb 2000 Series - Activated Carbon

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Inhalation.
Long term local effects.
1.84 mg of substance/m³

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Inhalation.
Long term local effects.
0.9 mg of substance/m³

Predicted no effect concentration (PNEC):

ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS) (CAS: 7440-44-0)
Environmental compartment: Soil.
PNEC : 10 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Local exhaust ventilation is recommended.

For the use of Granular Activated Carbon, no risk management measures are mandatory, but only recommended.

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- Natural latex

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling dust.

Type of FFP mask :

Wear a disposable half-mask dust filter in accordance with standard EN149/A1.

Category :

- FFP2

Particle filter according to standard EN143 :

- P (White)

Exposure controls linked to environmental protection

Local exhaust ventilation to remove material at source.

Contained storage.

Regulated waste disposal.

AquaSorb 2000 Series - Activated Carbon

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Solid in granules.

Colour

Black

Odour

Odour threshold : Not stated.

None

Melting point

Melting point/melting range : Not relevant.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not relevant.

Flammability

Flammability (solid, gas) : NC

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : NC

Explosive properties, upper explosivity limit (%) : NC

Flash point

Flash point interval : Not relevant.

Auto-ignition temperature

Self-ignition temperature : Not relevant.

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

pH

pH (aqueous solution) : 7-11

pH : Not stated.

Slightly basic.

Kinematic viscosity

Viscosity : NA

Solubility

Water solubility : Insoluble. 0
Method for determining the water solubility :
OCDE Guideline 105 (Water solubility).

Fat solubility : 0

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : NA

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : 200-700 kg/m³

AquaSorb 2000 Series - Activated Carbon

Method for determining the density :
ASTM D2854

Relative vapour density

Vapour density : NA

9.2. Other information

Physical and chemical properties of the saturated activated carbon may be different from the virgin material.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

Evaporation rate

Evaporation rate : NA

Miscibility

Miscibility : NA

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

This product shows no reactivity under the specified conditions of storage, shipment and use.

10.2. Chemical stability

This substance is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

In contact with solvents and strong oxidisers.

10.4. Conditions to avoid

Avoid :

- formation of dusts
- heating
- heat
- humidity

Dusts can form an explosive mixture with air.

10.5. Incompatible materials

Keep away from :

- strong oxidising agents
- combustible material
- strong acids
- solvents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

AquaSorb 2000 Series - Activated Carbon

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

In the event of dust formed by mechanical action (sanding, sawing, etc.), this dust may cause irritation by inhalation and contact with eyes.

11.1.1. Substances

Based on the physical and chemical properties of activated carbons, the absence of effects on toxicological studies and the therapeutic use of activated carbons as adsorbing agents for the treatment of acute poisoning and acute diarrhoea, it can be expected that Activated Carbon is not absorbed via the oral, dermal and inhalation routes.

Acute toxicity :

ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS) (CAS: 7440-44-0)
Oral route : LD50 > 2000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 423 (Acute Oral toxicity Acute Toxic Class Method)

Inhalation route (Dusts/mist) : LC50 > 64.4 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/skin irritation :

ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS) (CAS: 7440-44-0)
Species : Rabbit
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious damage to eyes/eye irritation :

ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS) (CAS: 7440-44-0)
Corneal haze : Average score = 0.00
Species : Rabbit
Duration of exposure : 72 h
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Iritis : Average score = 0.00
Species : Rabbit
Duration of exposure : 72 h
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Conjunctival redness : Average score = 0.67
Species : Rabbit
Duration of exposure : 72 h
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Conjunctival oedema : Average score = 0.33
Species : Rabbit
Duration of exposure : 72 h
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitisation :

- Skin : Not sensitising.
- Inhalation : No information available

ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS) (CAS: 7440-44-0)
Local lymph node stimulation test : Non-Sensitiser.

AquaSorb 2000 Series - Activated Carbon

Species : Mouse
OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity :

All the key studies indicate that the substance does not show any genotoxic potential. Therefore, it can be concluded that the substance is not mutagenic and does not need to be classified for mutagenicity according to the criteria outlined in Annex I of 1272/2008/EC (CLP / EU GHS) and Annex VI of 67/548/EEC (DSD/DPD).

ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS) (CAS: 7440-44-0)

Mutagenesis (in vitro) :

Negative.

Species : Bacteria

OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Ames test (in vitro) :

Negative.

With or without metabolic activation.

Species : S. typhimurium TA1535

Carcinogenicity :

No data available

Reproductive toxicant :

No data available

Specific target organ systemic toxicity - single exposure :

ACTIVATED CARBON - HIGH DENSITY SKELETON (AC-HDS) (CAS: 7440-44-0)

Oral route :

C > 2000 mg/kg bodyweight/day

Species : Rat

11.2. Information on other hazards

No data available

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

As Activated Carbon is insoluble in water, no toxicity is expected.

12.2. Persistence and degradability

Activated Carbon - HDS type is a refractory material and not amenable to break down by any natural chemical or enzymatic processes.

AC - HDS cannot be rendered into a soluble form capable of being absorbed.

Therefore it cannot find its way to any cell site where it could be conceivably be biodegraded.

12.3. Bioaccumulative potential

The substance has a very low potential to bioaccumulate in aquatic species (e.g. fish), i.e. a BCF < 10.

The substance has no log Kow, the substance size will impede passing membranes (particles with size > 0.5µm) and is not soluble in water. The bioaccumulation study is thus infeasible.

12.4. Mobility in soil

No data available, as the substance is insoluble.

12.5. Results of PBT and vPvB assessment

According to the ECHA Guidance on chemical safety assessment, Chapter R11, section R11.1.2.1: "The PBT and vPvB criteria of Annex XIII to the Regulation do not apply to inorganic substances". As Activated Carbon - HDS type is to be considered as an inorganic substance, the PBT assessment is not applicable.

12.6. Endocrine disrupting properties

No data available.

AquaSorb 2000 Series - Activated Carbon

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the substance and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

14.1. UN number or ID number

1362

14.2. UN proper shipping name

UN1362=CARBON, ACTIVATED

14.3. Transport hazard class(es)

- Classification :

4.2

- Exemption

ADR/RID: special provision 646

IMDG: special provision 925

> Steam activated carbon

IATA: special provision A3

> Does not meet the defined criteria, after having been submitted to the 4.2 test (UN Manual of Tests and Criteria (§ 33.4.3.3))

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	4.2	S2	III	4.2	40	0	646	E1	4	E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	4.2	-	III	0	F-A. S-J	223 925	E1	Category A SW1 H2	-	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	4.2	-	III	472	0.5 kg	472	0.5 kg	A3	E1	
	4.2	-	III	Forbidden	Forbidden	-	-	A3	E1	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For exempted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

AquaSorb 2000 Series - Activated Carbon

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

Container information:

No data available.

Particular provisions :

No data available.

15.2. Chemical safety assessment

A chemical safety assessment according to the rules stipulated in REACH directive has been performed. The appendices provide an overview of the risk management measures as based on this assessment.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the substance and not as a guarantee of the properties thereof.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.